



Product Service

CERTIFICATE

No. Z1A 029312 0032 Rev. 00

Holder of Certificate: **KEMMLIT-Bauelemente GmbH**

Maltschachstr. 37
72144 Dußlingen
GERMANY

Certification Mark:



Product:

Screens
Cubicle partitions in sanitary rooms

Tested according to:

PPP 52192B:2020
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713254444-1

Valid until: 2027-07-27

Date, 2022-07-29

(Ulrich Sommer)

CERTIFICATE

No. Z1A 029312 0032 Rev. 00

Model(s): **NiUU one**
 NiUU F
 NiUU K

Parameters:

NiUU F	
Door- / Wallmaterial	Wood based panel melamine-coated, Material thickness 30 mm
Door hinge	Rebated impact with solid aluminium edge
Door height	Height 2135 mm with 150 mm floor clearance (for room height version with top section)
Height	2135 mm; Special heights max 2800 mm
Cubicle depth	1500 mm (Nominal dimension)
Door width	570 mm (Nominal dimension) 650 mm (Nominal dimension) 750 mm (Nominal dimension) 980 mm (Nominal dimension) Special widths possible

NiUU K	
Door- / Wallmaterial	Wood based panel melamine-coated Material thickness 38 mm Partition walls 30 mm
Door hinge	Rebated impact with solid aluminium edge
Door height	Height 2135 mm with 150 mm floor clearance (for room-high version max. 2800 mm)
Height	2135; with 150 mm floor clearance (for room-high version max. 2800 mm)
Cubicle depth	1500 mm (Nominal dimension)
Door width	570 mm (Nominal dimension) 650 mm (Nominal dimension) 750 mm (Nominal dimension) 980 mm (Nominal dimension)



CERTIFICATE

No. Z1A 029312 0032 Rev. 00

NiUU one F & NiUU one K	
Door- / Wallmaterial for NiUU one F	Wood based panel melamine-coated Material thickness 38 mm Partition walls 30 mm e.g. composite plate
Door- / Wallmaterial for NiUU one K	Wood based panel melamine-coated Material thickness 38 mm Partition walls 30 mm
Door hinge	butt hinged with ABS-edge
Height	2000 mm incl. 150 mm floor clearance Special heights max. til 2800 mm
Cubicle depth	1500 mm (Nominal dimension)
Door width	570 mm (Nominal dimension) 640 mm (Nominal dimension) 750 mm (Nominal dimension) 980 mm (Nominal dimension)