



Product Service

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Holder of Certificate: **KEMMLIT-Bauelemente GmbH**

Maltschachstr. 37
72144 Dußlingen
GERMANY

Certification Mark:



Product:

Screens
Cubicle partitions in sanitary rooms

Tested according to:

PPP 52192B:2020
AfPS GS 2019:01 PAK

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713254444-2

Valid until: 2027-07-27

Date, 2022-07-29

(Ulrich Sommer)

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Model(s): B-Bambino-Exclusive
B-Bambino Classic
D-Bambino Classic
BK-E-Bambino-Exclusive
BK-E Bambino Classic
DK-E-Bambino Classic

Parameters:

General

Height: 1400 mm (B-Bambino-Exclusive, B-Bambino Classic, D-Bambino Classic),
1970 mm for adults (BK-E-Bambino-Exclusive, BK-E Bambino Classic, DK-E Bambino Classic)

Door widths: 470 mm, 520 mm, 570 mm (standard), 900 mm, doors opening outwards

Cubicle depth: 1100 mm (standard dimension)

Fittings: 3-roller-safety hinges, Ø 20 mm, with aluminium tubing finger protection

Door handles: safety ring handle made of impact resistant and break proof nylon with integrated rubber damper as door stop

Feet: Ø 20 mm, height-adjustable, made of aluminium powder-coated with stainless steel plate and tread-proof cover rosette made of nylon

Wall connections: Wall connections through stable aluminium panel holders, powder-coated or anodised, to compensate for construction tolerances.

Types B-Bambino-Exclusive and BK-E-Bambino-Exclusive

Walls: 13 mm solid grade panels according to DIN EN 438 (DIN 16926). The corners to avoid injuries are radius 33 mm rounded.

Doors: In the same construction as the walls, with safety finger pinch protection, made of continuous 20 mm wide soft lip finger pinch protection profile on the stop side and continuous made of continuous aluminium-finger pinch protection tube on the hing side.
Swing doors are not permitted.
Door opening only to the outside.

Ground clearance: 80 mm

CERTIFICATE

No. Z1A 029312 0031 Rev. 00

Types B-Bambino-Classic and BK-E-Bambino-Classic

- Walls: 13 mm solid grade panels according to DIN EN 438
(DIN 16926). The corners to avoid injuries are radius 33 mm rounded.
- Doors: In the same construction as the walls, with safety finger pinch protection, made of continuous 20 mm wide soft lip finger pinch protection profile on the stop side and continuous made of continuous aluminium-finger pinch protection tube on the hinge side.
Swing doors are not permitted.
Door opening only to the outside.
- Ground clearance: 120 mm or 89 mm

Types D-Bambino Classic and DK-E-Bambino Classic

- Walls: 30 mm thick melamine-coated solid chipboard.
All edges are protected with 2 mm thick ABS-glue (radius=2 mm)
All corners are rounded with a radius of 33 mm to prevent injuries.
- Doors: In the same construction as the walls, with safety finger protection finger protection, made of 20 mm wide rounded soft lip finger trap protection on the stop side and a continuous aluminium finger pinch protection tube on the hinge side
Swing doors are not permitted
Door opening only to the outside
- Ground clearance: 120 mm or 89 mm