



CERTIFICATE

No. Z1A 029312 0026 Rev. 00

Holder of Certificate: KEMMLIT-Bauelemente GmbH

Maltschachstr. 37 72144 Dußlingen GERMANY

Certification Mark:





Product: Screens

Partition walls for sanitary facilities

Tested according to: PPP 52192B:2020 AfPS GS 2019:01 PAK

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713181697-2

Valid until: 2025-04-19

Date, 2020-05-20

(Levke Koch)



CERTIFICATE

No. Z1A 029312 0026 Rev. 00

Model(s): variocell

softcell hardcell classiccell

Parameters:

Aluminium or stainless steel 2000 mm or 2135 mm incl. 150 mm ground clearance 1500 mm (up to 1601 mm with hit and foot) 570 mm (nominal size) 650 mm (nominal size=standard) 750 mm (nominal size) 980 mm (nominal size)
incl. 150 mm ground clearance 1500 mm (up to 1601 mm with hit and foot) 570 mm (nominal size) 650 mm (nominal size=standard) 750 mm (nominal size)
incl. 150 mm ground clearance 1500 mm (up to 1601 mm with hit and foot) 570 mm (nominal size) 650 mm (nominal size=standard) 750 mm (nominal size)
1500 mm (up to 1601 mm with hit and foot) 570 mm (nominal size) 650 mm (nominal size=standard) 750 mm (nominal size)
570 mm (nominal size) 650 mm (nominal size=standard) 750 mm (nominal size)
650 mm (nominal size=standard) 750 mm (nominal size)
750 mm (nominal size)
980 mm (nominal size)
1 1/
2000 mm or 2135 mm incl. 150 mm
Ground clearance (-10 / +25 mm)
up to 1600 mm divided with shadow gap
up top 1601 mm divided with shadow-gap push
and additional foot
from to 570 - 980 mm (nominal size)
•
2000 mm or 2135 mm
incl. 150 mm ground clearance
1500 mm (1601 mm with hit and foot)
570 (nominal size)
650 mm (nominal size=standard)
750 mm (nominal size)
980 mm (nominal size)